

# decotric Roller Wallpaper Adhesive GTV

## decotric Roll-Kleister GTV

High-quality, quick-soluble methyl cellulose paste

### Instructions for use:

*decotric Roller Wallpaper Adhesive GTV* is ideally suited for pasting non woven wallpaper by the new wallpapering technique (application of paste to the wall) or traditional wallpapering (application of paste to the wallpaper) and for pasting heavy wallpaper like textile wallpaper, glass fibre fabrics, embossed wallpaper, vinyl wallpaper, etc.

### Technical specification:

Compounds: Methyl cellulose, polyvinyl acetate powder  
 Density: Approx. 0.5 g/cm<sup>3</sup>  
 pH-value: Approx. 8  
 Solubility: Ready for use in 3 minutes  
 Usage: 200-300 ml/m<sup>2</sup>

### Surface preparation:

The surface has to be dry, firm and free of dust and grease. Remove old and loose wallpaper and distemper *decotric Wallpaper Remover*. Fill in cracks and holes with *decotric Interior or decotric Super Bond Filler*. Pre-treat highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free..* Insulate water-soluble impurities, which may show through when wallpapering with *decotric Insulating Spray*.

### Application:

Stirring vigorously, sprinkle *decotric Roller Wallpaper Adhesive GTV* into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx. 3 minutes and then stir vigorously again.

#### Applying to wallpaper:

Evenly coat the wallpaper with *decotric Roller Wallpaper Adhesive GTV* and fold the pasted ends together. After leaving to soften for sufficient time, hang the wallpaper with matching seams and press down.

#### Applying to the surface:

Use a lambs wool roller to evenly apply the mixed *decotric Roller Wallpaper Adhesive GTV* to the surface over a width of 1-2 wallpaper widths. Place the wallpaper strip directly into the fresh adhesive bed and uniformly press down. Follow up the seams with a smooth seam roller after a few minutes. To increase the moisture resistance and where hanging wallpaper on hardly absorbent surfaces we recommend adding 20 % *decotric Wallpaper and Border Adhesive*. Always follow the manufacturer's instructions for use. The paste is lime- and cement constant.

Do not use if the object and/or room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

### Mixing ratio:

For	Ratio	Volume of water	Needed for
<b>Application to surface</b> * non woven wallpaper * glass fibre wallpaper - laminated	1:17.5	3.5	Approx. 20 m <sup>2</sup>
<b>Application to wallpaper:</b> * Vinyl wallpaper * Fabric/textile wallpaper * Heavy wallpaper	1:20	4.0	20-25 m <sup>2</sup>

### Storage:

Store in a cool and dry place!

### Available sizes:

200 g collapsible box 020502001  
 500 g collapsible box 020504001

### Minimum durability:

5 years as of date of manufacture