## decotric MC Instant Wallpaper Adhesive - Special decotric MC Spezialkleister Instant

High-quality, fast-dissolving methylcellulose adhesive

Instructions for use:	<i>decotric MC Instant Wallpaper Adhesive - Special</i> is suited for woodchip wall- papers, light and heavy weight paper wallpapers, embossed wallpapers, textile wallpapers, vinyl wallpapers and similar wall coverings.				
Technical specifications:	Components:	methyl cellu	lose, polyvinyl acetat	e powder	
	Density:	0.45 g/cm <sup>3</sup>			
	pH-value:	approx. 8			
	Solubility:	ready to use	e in approx. 3 minutes		
	Usage:	approx. 150	0-200 ml/m²		
Surface preparation:	The surface must be dry, firm and free of dust and grease. Remove old, peelin wallpapers and distemper paints using <i>decotric Wallpaper Remover</i> . Make go cracks and holes using <i>decofill Interior</i> or <i>decomur Super Bonding Filler</i> . Prin highly absorbent, sanding and chalking surfaces with <i>decotric Deeply Penetring Primer – Solvent Free</i> .				
	Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using <i>decotric Insulating Spray</i> .				
	To make a subsequent change of wallpaper easier, we recommend priming the surface with <i>decotric Wallpaper Base Primer 'Tapeten-Wechselgrund'</i> , especially when hanging washable wallpapers.				
Application:	Stirring vigorously, sprinkle <i>decotric MC Instant Wallpaper Adhesive - Special</i> into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx. 3 minutes and then stir vigorously again.				
	Apply the adhesive to the wallpaper using a wallpapering machine or brush. Fold the pasted ends inwards and hang after an adequate soaking time. Hang the wallpaper according to the manufacturer's instructions.				
	We recommend to add 750 g <i>decotric Wallpaper and Border Adhesive</i> per 200 g packet <i>decotric MC Instant Wallpaper Adhesive - Special</i> for use on hardly absorbent surfaces and to increase the moisture resistance.				
	Do not use if the object and/or room temperature are below + 5° Celsius! Remove adhesive residues using a damp cloth. Clean tools in water after use.				
Mixing ratio:	for	Mixing ratio	Quantity of water per 200 g packet	Coverage of one packet	
	Pre-pasting	1:40	81	50-70 m²	
	Woodchip wallpapers Heavy wallpapers	1:25	5	25-30 m <sup>2</sup>	
	Special applications of wall covering	1:20	4	20-25 m²	
Storage:	Store in a cool and dry place	9!			
Available size:	200 g collapsible box	020202001			