

decotric Rigid-Foam Adhesive decotric Hartschaumkleber

Ready-made, solvent-free, water-based adhesive for bonding polystyrene and rigid-foam panels indoors

Instructions for use: *decotric Rigid-Foam Adhesive* is ideally suited for bonding decorative, exposed and insulating panels made of polystyrene, depron or rigid foam and Styrofoam battens and bonding layers.

Technical specification:

Components:	terpolymer plastic dispersion
Density:	approx. 1.66 g/cm ³
pH-value:	8 - 9
Volume required:	750 g/m ²

Surface preparation: The surface has to be absorbent, dry, firm and free of release agents (dust, grease, etc.). Remove loose plaster, old wallpaper and loose paint. Make good cracks and holes using *decomur Super Bonding Filler* or *decofill Interior*. Prime strongly absorbent, sanding or chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free*.

Application: Apply *decotric Rigid-Foam Adhesive* evenly to the surface with a tooth trowel (preferably B2 toothing). Lay in panels or strips to be bonded and press on evenly. For bondings at ceilings, the adhesive should be applied to the back of the ceiling panels.

When the adhesive has dried completely (1-2 days, depending on absorptive capacity of the surface), the bonded surfaces can be painted, wallpapered or smoothed over. In order to achieve an optimum adhesion of wallpaper to the bonded surfaces, it is recommended to apply a bond-bridging paint with a slurried adhesive (*decotric Rigid-Foam Adhesive* with 20 % water added).

Remove adhesive tailings with water immediately.
Do not use at surface and room temperatures of below + 5 C.
After use, clean tools with water.

Storage: Store in a cool place! Keep containers tightly sealed!

Available sizes:

4 kg PE-bucket	001002001
8 kg PE-bucket	001003001