

decotric PVC/CV and Carpet Adhesive decotric Kleber für Teppich und PVC

solvent-free, water-based adhesive

Instructions for use: decotric PVC/CV and Carpet Adhesive is suitable for gluing PVC/CV coverings,

needle felt as well as textile floor coverings with various backings. *decotric PVC/CV and Carpet Adhesive* is suitable for chair casters to DIN 68131 and for

screeds with floor heating.

Technical specifications: Components: terpolymer plastic dispersion, fillers, natural resin

ester

Density: approx. 1.30 g/cm³

pH value: 6-7

Usage: A2 indentations: 300-350 g/m² B2 indentations: 350-450 g/m²

GEV-EMICODE: EC 1 – very low emission

Surface preparation: The surface must be firm, permanently dry, and free of cracks and release

agents. Remove any unevenness using AKAPLAN Smoothing Compound for floorings or AKAFLEX Smoothing Compound for wooden floorings. Prime highly absorbent and sanding surfaces using decotric Deeply Penetrating Primer —

Solvent Free.

Application: Absorbent surfaces

Evenly apply decotric PVC/CV and Carpet Adhesive on absorbent surfaces or steam permeable floor coverings with a spreading comb (A2 for PVC and foam backings, B2 for jute backings) and leave for dry for 10-20

minutes and then place the flooring in the adhesive bed.

Impermeable surfaces:

By PVC-, PVC flooring and other impermeable surfaces leave for dry until the adhesive is completely dry (30-60 minutes) and then place the flooring in the adhesive had it is possible to world PVC floorings after 24 hours.

adhesive bed. It is possible to weld PVC floorings after 24 hours.

The ventilation depending on the absorbency of the surface, the ambient tem-

perature and air humidity.

Follow the flooring manufacturer's laying instructions. Immediately remove any adhesive residues with water.

Clean tools in water immediately after use.

Do not use if the surface and/or room temperature are below + 10° Celsius!

Storage: Store in a cool place! Keep the containers tightly sealed!

Catalogue no: 095

Available sizes: Art. no 001501001 750 g PE tin

Art. no 001502001 3 kg PE tub Art. no 001503001 5 kg PE tub Art. no 001504001 10 kg PE tub