## decotric Fleece Fixative for fitted carpets decotric Vliesfixierung fuer Teppichboeden

Ready to use, solvent-free fixative for carpeting with non-bonded backings.

| Instructions for use:     | <i>decotric Fleece Fixative for fitted carpets</i> is suitable for fixing carpeting with non-bonded backings. It can be used on all interior surfaces such as tiles, cement screed, PVC floorings, floor smoothing compound, etc. Can also be used for heated floor constructions.   |  |  |
|---------------------------|--|--|--|
|                           | When using on parquet, a   | waterproof seal has to be applied first.   |  |
| Technical specifications: | Components:  | Synthetic resin emulsion, natural resin derivatives, fillers   |  |
|                           | Density:   | approx. 1.2 g/cm <sup>3</sup>  |  |
|                           | pH-value:  | 8-9  |  |
|                           | Usage:   | 200-300 g/m²   |  |
|                           | GISBAI GISCODE:  | D 1  |  |
| Preparation of surface:   | The surface must be permanently dry, firm, moisture resistant and free of re-<br>lease agents (grease, dust, etc.) Even out cracks, holes, unevenness as well as<br>rough screed using AKAPLAN Flooring Smoothing Compound or AKAFLEX<br>Wood Flooring Smoothing Compound. Pretreat highly absorbent and sanding<br>surfaces using decotric Deeply Penetrating Primer – Solvent Free.  |  |  |
| Instructions for use:     | Evenly apply <i>decotric Fleece Fixative for fitted carpets</i> to the surface using a spreading comb (A2 indentations) or lambswool roller.<br>After a drying time (i.e. solvent evaporation time) of approx. 30 minutes, lay the covering and rub down well. It is also possible to lay the floor covering immediately after applying the bonded fibre fixative, whereby the edges and joints then have to be rubbed down again after approx. 30 minutes. Observe the covering manufacturer's laying instructions. |  |  |
|                           |  |  |  |
|                           | Do not use if the surface a  | mmediately remove residual adhesive with water.<br>Do not use if the surface and/or room temperature are below + 10° Celsius!<br>Clean tools in water immediately after use.<br>After removing the flooring the residue bonded fibre fixative can be easily re-<br>noved with hot water to which <i>decotric Wallpaper Remover</i> has been added.<br>The exposure time is approx. 15 minutes. Then scrape off the softened fixative<br>using a stopping knife and thoroughly wash down the whole area with water. |  |
|                           | moved with hot water to with the exposure time is appr   |  |  |
| Storage:                  | Store in a cool place! Keep containers tightly sealed!   |  |  |
| Available sizes:          | 5 kg PE tub  | 021002001<br>021003001<br>021004001  |  |