

decotric Bonding Fixative decotric Haftfixierung

Ready to use, solvent-free fixative for floor coverings with fleece backing.

Instructions for use: *decotric Bonding Fixative* for carpets is suitable for the fixation of carpets with fleece backing as well as for PVC and CV covering. Glueing can be done on all water-resistant surfaces in indoor areas like tiles, cement screed, PVC floors, floor-levelling mass, etc. It can also be used for heated floor structures. There must be waterproof sealing should gluing on parquet be desired.

Technical data:

Components:	Synthetic resin dispersion, dispersion of modified resins, additives
Density:	approx. 1.0 g/cm ³
pH value:	7-8
Consumption:	100-200 g/m ²
GISBAU GISCODE:	D1

Surface preparation: The surface must be permanently dry, stable, humidity-resistant and free from parting compounds and contaminations (grease, dust, etc.). Level out cracks, holes, irregularities in thickness as well as rough screeds using *AKAPLAN Floor Levelling Compound*, *AKAFLEX Floor Levelling Compound* or *decofill External*. Pretreat strongly absorbent and sanding surfaces with *decotric Deeply Penetrating Primer - solvent free*.

Application: Cut flooring to size. Turn over one half and then apply *decotric Bonding Fixative* evenly onto the surface using a short-piled lambskin roller and allow it to evaporate completely until a transparent adhesive film has developed.

The drying time is between 30 and 60 minutes, depending on surface absorbing capacity, temperature and air humidity. The film must be transparent before the flooring can be laid in. The laid flooring must be thoroughly rubbed down afterwards. Do the same with the other half. Weight edges and joints down at the beginning if required. Apply at least approx. 200 ml/m² in the case of PVC and CV coverings.

Removal: The rest of the fixing emulsion can be easily removed using warm water under addition of *decotric Wallpaper Remover* after the floor covering has been removed. The contact time is approx. 15 minutes. Afterwards, remove the detached fixation using a plastic spatula and rinse the whole surface thoroughly with water.

The laying instructions of the floor covering manufacturers must be complied with.

Remove adhesive residues with water.
Do not process below +10 °C sub-floor and room temperature.
Clean any working equipment with water after use.

Storage: Keep cool but protected from frost! Keep container well closed!

Available sizes:

2.5 kg	021102001
5.0 kg	021103001