

## decotric Fine Filler decotric Feinspachtel

Ready to use, solvent-free synthetic resin knifing filler for indoor use.

Instructions for use: decotric Fine Filler is ideally suited as surface pretreatment of wood for subse-

quent coating with acrylic and alkyd resin varnishes. Surfaces made from concrete, gypsum, clay tiles and similar mineral building materials are also suitable. *decotric Fine Filler* is easy to use, highly filling and very easy to sand down.

Not suitable for filling work on metals, glass and plastics.

**Technical specifications:** Basic raw materials: Pure acrylate emulsion, fillers

Density: approx. 1.80 g/cm<sup>3</sup>

pH-value: 7.5-8.5

Consumption: approx. 1.8 kg/m² for 1 mm thick filler layer

GISBAU product code: M-DF01

Preparation of surface: The surface must be dry, firm and free of release agents (grease, dust, etc.).

Pretreat highly absorbent, sanding or chalking mineral surfaces with decotric

Deeply Penetrating Primer - Solvent Free.

Prime untreated and highly absorbent wood with wood precoat paint or varnish.

Instructions for use: Knead the tube well before use. Apply all layer of decotric Fine Filler using a

stopping knife (e.g. Japan stopping knife) up to max. 3 mm thick. The fully-dried filler layer (after approx. 1 hour) is easy to sand down or grind and can be coated over with all standard, commercial acrylic and alkyd resin varnishes as well

as emulsion paints.

Do not use on surfaces or in rooms below + 5° Celsius!

Clean tools with water immediately after use.

Storage: Store in a dry and frost-free place! Keep the containers tightly sealed!

Available size: 400 g PE tube 033401001