

decotric Algae and Mould STOP decotric Algen- und Schimmel-STOP

Free of active chlorine, therefore odourless – for use indoors

Instructions for use: Removes mould, algae and moose in interior areas – for example in sanitary

installations. Cleans house walls, floors, roofs, garages, wood, tiles, clay tiles, stone, and concrete, etc. Can also be used as a cleaning surface pre-treatment

for subsequent coats and facade impregnations.

Technical specifications: Components: Didecyl dimethyl ammonium chloride

Density: 1.00 g/cm³ pH-value: 7 - 8

Usage: 100-200 ml/m²

Application: Directly spray decotric Algae and Mould STOP onto the affected area from a

distance of approx. 15-20 cm and leave to act. This occurs within 1-3 days. In case of severe contaminations, if no optical change appears in the treated surface, apply a further coat of decotric Algae and Mould STOP. Wash off any

residues using clean water.

Important information: Please see the EU Safety Data Sheet for all safety-related data (EU-

CLP).

Storage: Store in a cool but frost-free place! Keep the containers tightly sealed!

Available sizes: 500 ml PE spray bottle 007002001