

decotric MC Power Adhesive Woodchip Special

decotric MC Rauhfaser KRAFT-Kleister spezial

High quality, resin-reinforced methylcellulose adhesive with highly humidity resistant.

Instructions for use: *decotric MC Power Adhesive Woodchip Special* is suited for all standard commercial wallpaper such as paper wallpapers, embossed wallpapers vinyl wall-papers etc. Due to the distinctive of the highly humidity resistant *decotric MC Power Adhesive Woodchip Special* is excellently usable for painting over cash structure wallpapers and woodchip papers.

Technical specifications:

Components:	methyl cellulose, synthetic resin powder
Density:	0.55 g/cm ³
pH-value:	approx. 8
Solubility:	ready to use in approx. 10-15 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*. Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. To make a subsequent change of wallpaper easier, we recommend priming the surface with *decotric Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especially when hanging washable wallpapers.

Application: Stirring vigorously, sprinkle *decotric MC Power Adhesive Woodchip Special* into clean, cold water (see table) and continue to stir for a few minutes. Leave for 10-15 minutes and then stir vigorously again.

Apply the adhesive to the wallpaper using a wallpapering machine or brush, Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use. Do not apply subsequent coats of paint until the adhesive has completely dried.

We recommend adding 750 ml *decotric Wallpaper and Border Adhesive* per 200 g packet *decotric MC Power Adhesive Woodchip Special* for use on hardly absorbent surfaces and to increase the moisture resistance.

The paste is lime- and cement constant.

Do not use if the object and/or room temperature are below + 5° Celsius!
Clean tools with water immediately after use.
Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 200 g packet	Coverage of a 200 g packet
Pre-pasting	1:40	8 l	60-80 m ²
Woodchip wallpaper	1:20	4 l	20-25 m ²
Embossed wallpapers	1:20	4 l	20-25 m ²
Wallpapering machine	1:25	4,5 l	25-30 m ²

Storage: Store in a dry and cool place!

Available sizes:

200 g collapsible box	020402001
500 g collapsible box	020403001