

decotric MC Wallpaper Adhesive G20 for Wallpapering Machines - instant decotric MC Geraetekleister G 20 – instant

High quality, quick-dissolving, wallpapering machine adhesive made from methylcellulose and synthetic resin.

Instructions for use: *decotric MC Wallpaper Adhesive G20 for Wallpapering Machines - instant* is ideally suited for reliable, secure pasting of vinyl wallpapers, structured vinyl wallpapers, woodchip wallpapers, heavyweight paper wallpapers, embossed wallpapers, textile wallpapers and similar wall coverings. Ideally suited for use with standard commercial wallpapering machines.

Technical specifications:

Components:	methyl cellulose, synthetic resin powder
Density:	0.55 g/cm ³
pH-value:	approx. 8
Solubility:	ready to use in approx. 5 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*. Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. To make a subsequent change of wallpaper easier, we recommend priming the surface with *decotric Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especially when hanging washable wallpapers.

Instructions for use: Stirring vigorously, sprinkle *decotric MC Wallpaper Adhesive G20 for Wallpapering Machines – instant* into clean, cold water (see table) and continue to stir for a few minutes. Leave for 5 minutes and then stir vigorously again.

Apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

We recommend to add approx. 20 % *decotric Wallpaper and Border Adhesive* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the object and/or room temperature are below + 5° Celsius!
Clean tools with water immediately after use.
Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 750 g packet	Coverage of a 750 g packet
Pre-pasting	1:40	30 l	approx. 250-300 m ²
Wallpapering machine	1:20	15 l	approx. 75 m ²
Woodchip wallpaper	1:20	15 l	approx. 75 m ²
Heavy wallpapers, textile, embossed + vinyl wallpapers	1:20	15 l	approx. 75 m ²

Storage: Store in a cool and dry place!

Available sizes:

300 g collapsible box	022601001
750 g collapsible box	022602001