

decotric Wallpaper Adhesive – Special decotric Spezialkleister

High-quality super special methylcellulose adhesive

Instructions for use: *decotric Wallpaper Adhesive – Special* is a professional adhesive for all vinyl, embossed vinyl, woodchip and embossed wallpapers and heavy wallpapers.

Technical specifications:

Components:	Starch ether, poly vinyl acetate powder
Density:	approx. 0.50 g/cm ³
pH-value:	approx. 8
Solubility:	Ready for use after approx. 30 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*. Pre-treat highly absorbent, sanding and chalking surfaces using *decotric Deeply Penetrating Primer – Solvent Free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*.

To make a subsequent change of wallpaper easier, we recommend priming the surface first with *decotric Wallpaper Base Primer ‘Tapeten-Wechselgrund’*, especially where washable wallpapers are used.

Application: Stirring vigorously, sprinkle *decotric Wallpaper Adhesive – Special* into clean, cold water and continue to stir for a few minutes. Leave for 30 minutes and then stir vigorously again.

Apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpaper manufacturer’s instructions for use.

We recommend to add 750 g *decotric Wallpaper and Border Adhesive* per 200 g packet *decotric Wallpaper Adhesive – Special* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!
Remove adhesive residues using a damp cloth.
Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1:40	8 l	60-80 m ²
Heavy wallpapers	1:20	4 l	22-26 m ²
Woodchip wallpaper	1:20	4 l	22-26 m ²
Special bonding situations	1:15	3 l	10-15 m ²

Storage: Store in a cool and dry place!

Available size: 200 g collapsible box 000202001