

aka Wallpaper Adhesive - Normal aka Tapetenkleister Normal

Economy priced wallpaper adhesive, quality-tested.

aka Wallpaper Adhesive - Normal is suitable for pasting lightweight wallpapers. Instructions for use:

Technical specifications: Components: Carboxy methyl cellulose, starch ether

> approx. 0.40 g/cm3 Density:

pH-value: approx. 8

Solubility: Ready for use in 30 minutes

Usage: approx. 200 ml/m²

The surface must be dry, firm, dust and free of release agents (dust, grease, Surface preparation:

> etc.) Remove all old, loose wallpapers and distempers using decotric Wallpaper Remover. Make good cracks and holes using decofill Interior or decomur Super

Bonding Filler.

Pre-treat strongly absorbent, abrasive and chalky surfaces with decotric Deeply Penetrating Primer - Solvent Free. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using decotric Insulating Spray. We recommend a first coat with decotric Wallpaper Primer white if hanging highly translucent wallpapers and where surfaces are

highly contrasting.

Instructions for use: Stirring vigorously, sprinkle aka Wallpaper Adhesive - Normal into clean, cold

water (see table) and continue to stir for a few minutes. Leave for approx 30

minutes and then stir vigorously again.

Evenly apply aka Wallpaper Adhesive - Normal to the wallpaper using a brush or wallpapering machine, fold the pasted ends inwards and hang after an adequate soaking time. Hang the wallpaper according to the manufacturer's instruc-

tions.

Clean tools with water immediately after use.

Do not use if the object and/or room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 125 g packet	Coverage of a 125 g packet
Pre-pasting	1:65	81	50-60 m ²
Lightweight wallpapers	1:48	61	35 m²
Heavy wallpapers	1:40	51	30 m²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box 002801080