

## aka Wallpaper Adhesive - Special aka Spezialkleister

Instructions for use: aka Wallpaper Adhesive - Special is suitable for pasting woodchip wallpapers,

paper wallpapers, vinyl wallpapers and similar wall coverings.

**Technical specifications:** Components: Starch ether, polyvinyl acetate powder

Apparent weight: approx. 0.50 g/cm<sup>3</sup>

pH-value: approx. 8

Solubility: ready for use after approx. 30 minutes

Usage: approx. 200 ml/m<sup>2</sup>

Surface preparation: The surface must be dry, firm, dust and free of release agents (dust, grease,

etc.) Remove all old, loose wallpapers and distempers using decotric Wallpaper Remover. Make good cracks and holes using decofill interior or decomur Super

Bonding Filler.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *decotric Deeply Penetrating Primer – Solvent Free.* Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using decotric Insulating Spray.

decotric Insulating Spray.

To make a subsequent change of wallpaper easier, we recommend priming the surface with *decotric Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especial-

ly when hanging washable wallpapers.

Application: Stirring vigorously, sprinkle aka Wallpaper Adhesive - Special into clean, cold

water and continue to stir for a few minutes. Leave for approx. 30 minutes and

then stir vigorously again.

Evenly apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufactur-

er's instructions for use.

We recommend to add 750 g decotric Wallpaper and Border Adhesive per 200 g packet aka Wallpaper Adhesive - Special for use on hardly absorbent surfac-

es and to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1:40	8	60-80 m <sup>2</sup>
Heavy wallpapers	1:20	4	22-26 m <sup>2</sup>
Woodchip wallpapers	1:20	4	22-26 m <sup>2</sup>
Special adhesive tasks, unprinted embossed wallpa- pers	1:15	3	10-15 m²

Storage: Store in a cool and dry place!

**Available size:** 200 g collapsible box 002901000