

KVS Cellulose Wallpaper Adhesive KVS Zell-Leim

Wallpaper adhesive of reliable, tested quality.

Instructions for use: KVS Cellulose Wallpaper Adhesive is suited for woodchip wallpapers, light and

heavy weight paper wallpapers, embossed wallpapers, textile wallpapers, vinyl

wallpapers and similar wall coverings.

Technical specifications: Components: Carboxmethylcellulose

Density: 0.6 g/cm³ pH-value: 7-8

Solubility: ready to use in approx. 30 minutes

Usage: Approx 200 ml/m²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling

wallpapers and distemper paints using decotric Wallpaper Remover. Make good

cracks and holes using decofill Interior or decomur Super Bonding Filler.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *decotric Deeply Penetrating Primer – Solvent Free.* Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using

decotric Insulating Spray.

To make a subsequent change of wallpaper easier, we recommend priming the surface first with decotric Wallpaper Base Primer 'Tapeten-Wechselgrund',

especially where washable wallpapers are used.

Application: Stirring vigorously, sprinkle 200 g KVS Cellulose Wallpaper Adhesive into 5 l

clean, cold water and continue to stir for a few minutes. Leave for approx. 30

minutes and then stir vigorously again.

Evenly apply KVS Cellulose Wallpaper Adhesive to the wallpaper using a wallpapering machine or brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpa-

per manufacturer's instructions for use.

We recommend to add approx. 20 % decotric Wallpaper and Border Adhesive for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the object and/or room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Storage: Store in a cool and dry place! Keep the bag tightly sealed

Available sizes: 200 g paper bag 002402000

7.5 kg paper bag 002403000 25 kg paper bag 002401000