

decotric Lining Paper Paste

decotric Fein-Makulatur

The ideal preparation for wallpaper work on rough surfaces.

Instructions for use:	<i>decotric Lining Paper Paste</i> can be applied on all mineral surfaces such as gypsum plaster, lime and cement plaster, concrete and the like. Using <i>decotric Fine Surface Renovating Filler</i> will yield smooth, neutral, slightly absorbent surfaces for subsequent wallpaper work.	
Technical specification:	Components:	Wood fibres, thickeners
	Bulk weight:	0.46 g/cm ³
	pH value:	approx. 8
	Mixing ratio:	Spreadable primer: 500 g powder in 3 l of water Spread. primer: 500 g powder in 2 – 2.5 l of water Spray primer: 500 g powder in 4 l of water
	Consumption:	500 g powder are enough for approx. 10 m ²
Surface preparation:	The surface must be dry, stable and free from parting compounds (dust, grease, etc.). Prime sanding and chalking surfaces with <i>decotric Deeply Penetrating Primer - solvent free</i> . Mend cracks and holes with <i>decofill Interior</i> or <i>decomur Super Bonding Filler</i> .	
Application:	Fill clear cold water into a clean vessel, gradually adding <i>decotric Lining Paper Paste</i> while stirring and keep on stirring for a short while. Leave the formulation soak for approx. 30 minutes, then mix well again. Apply the prepared compound evenly onto the surface using a brush or spattle and let it completely dry. The surfaces may be re-sanded before wallpapering when required. <i>decotric Lining Paper Paste</i> can be processed with commercially available airless equipment. In this case, the volume of water should be increased to 4 l per 500 cell primer. Clean any working equipment with water after use.	
Storage:	Keep dry! Keep container tightly sealed!	
Available sizes:	1 kg	004002001