

decotric Styrofoam adhesive

decotric Styropor- und Renoviervlies-Kleber

Ready to use emulsion-based adhesive for interior polystyrene panels.

Instructions for use *decotric Styrofoam Adhesive* is suitable for gluing polystyrene panels, under-wallpaper, visible, décor and insulating panels made from polystyrene, and decorative strips, etc.

Technical specifications:

Components:	Styrene acrylate emulsion, fillers, thickening agents
pH-value:	approx. 8-9
Density:	approx. 1.70 g/cm ³
Usage:	approx. 750 g/m ² (B2 indentations)

Surface preparation: The surface must be absorbent, dry, firm and free of release agents (dust, grease, etc.) Remove loose masonry, old wallpaper and flaking paint. Make good cracks, holes and unevenness using *decomur Super Bonding Filler* or *decofill Interior*. Pretreat highly absorbent, sanding and chalking surfaces using *decotric Deeply Penetrating Primer – Solvent Free*.

Application: Evenly apply *decotric Styrofoam Adhesive* to the surface using a spreading comb (B2 indentations). Place the panels to be glued on in the moist, adhesive bed and press. Where used for gluing onto ceilings we recommend you apply the adhesive to the back of the panels.

The pasted areas can be painted, wallpapered or stoppered after the adhesive has completely dried. To guarantee optimum adhesion of wallpapers and paints on polystyrene, a primer coat of thinned polystyrene adhesive (with 20 % water added) should be applied with a roller.

Immediately remove residual adhesive with water
Do not use if the surface and/or room temperature are below + 5° Celsius!
Clean tools in water after use.

Storage: Store in a cool but frost-free place! Keep containers tightly sealed!

Available sizes:

1 kg PE can	001101001
4 kg PE tub	001102001
8 kg PE tub	001103001
14 kg PE tub	001104001