

decomur Exterior Façade Filler

decomur aussen Fassaden-Spachtel

Weatherproof, synthetic resin modified, cement-based joint filler for indoor and outdoor use.

Instructions for use:

decomur Exterior Façade Filler is ideally suited for making good, smoothing, levelling and coating all mineral surfaces such as lime and cement based plaster, gypsum plaster, concrete, aerated concrete, clay tiles, etc. The filled areas are easy to smooth off and felt.

Not suitable for levelling out floors and for filling works on wood, metal, plastic, and glass or coats of emulsion paint.

Technical Specifications:

Basic raw materials:	Synthetic resin, methyl cellulose, white cement
Bulk density:	approx. 1.10 g/cm ³
pH-value:	12-13
Mix ratio:	2.25 parts by volume powder to 1 part by volume water (e.g. 1 kg powder in 350 ml water)
Consumption:	1.2 kg powder per m ² with thickness of 1 mm
Working time:	approx. 30 minutes
Tensile bending strength:	4.0 N/mm ² to EC 18555, T. 3
Compressive strength:	11.0 N/mm ² to EC 18555, Part 3
Low in chromates according to EN 196-10	

Preparation of surface:

The surface must be firm and free from release agents (dust, formwork oil, etc.) Remove flaking paints and loose plaster. Prime very smooth concrete as well as highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer Solvent Free* or *LH Universal*.

Instruction for use:

Pour clean, cold water into a container and sprinkle in *decomur Exterior Façade Filler*. Stir vigorously until a smooth, lump-free mortar results. Use the stirred joint filler within 30 minutes. Unevenness can be smoothed while moist or felted after approx. 90 minutes.

Do not apply subsequent coats and fixings until the treated surface has fully dried. Always observe the paint and adhesive manufacturer's instructions for the pre-treatment of cement bound surfaces (e.g. fluorinate with *OLAFIRN*).

Do not use if the surface and/or room temperature are below +5° Celsius. Clean tools in water immediately after use

Important information:

.Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Store in a dry place! Keep the containers tightly sealed!

Available sizes:

5 kg paper bag	033905001
25 kg paper sack	033906001