

decotric Smoothing Filler

decotric Glaett- und Fuellspachtel

Gypsum-based smoothing compound reinforced with cellulose for indoor use. decotric Smoothing Filler is ideally suited for smoothing large areas in interior finishing work.

Instructions for use:

decotric Smoothing Filler is suitable for all filling and smoothing works on mineral surfaces such as plaster, concrete, aerated concrete, stone, etc. as well as for filling gypsum boards joints.

Do not use on glass, plastic, wood, metal and emulsion surfaces.

Technical specifications:

Basic raw materials:	Natural gypsum, methyl cellulose
Bulk density:	approx. 0.75 g/cm ³
pH-value:	7-8
Mix ratio:	1.8-2.0 parts by volume of powder to 1 part by volume of water (e.g. 1 kg powder in 650 ml of water)
Consumption:	1 kg powder per 1 m ² for 1 mm thick layer
Working time:	approx. 60 minutes at 20° Celsius
Fire behaviour :	A2 – s1, according to EN 13501
Bending tension strength:	92 N to EN 13963, 5.8.2. bending test 208 N to EN 13963, 5.8.1. tensile test
CE-certification according to EN 13963-3B	
CE-certification according to EN 13279-C7/20/2	

Preparation of surface:

The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.). Remove old wallpapers, peeling coats of paint and loose plaster. Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free*.

Instructions for use:

Fill cold, clean water into a clean container and sprinkle in *decotric Smoothing Filler*. Stir vigorously so that a smooth, lump-free mortar results. Use a firmer consistency than for smoothing large areas to fill cracks and holes.

The smoothing compound can be applied using a stopping knife or a trowel after 2-3 minutes' maturing time. Small uneven areas can be removed using a wet sponge board before the product has completely dried. After the product has completely dried, it is possible to sand down the smoothed area.

To avoid uneven drying of subsequent coats of paint where areas have been made good, it may be necessary to prime the areas made good or even the whole surface using *decotric Deeply Penetrating Primer – Solvent Free*. Clean tools in water immediately after use.

Storage:

Store in a dry place! Keep containers tightly sealed!

Available sizes:

5 kg paper bag	003201001
10 kg paper sack	003202001
25 kg paper sack	003203001