

decotric fast-setting Cement

decotric Blitzzement

Rapid curing, weather resistant repair mortar for use indoors and outdoors.

Instructions for use: *decotric fast setting Cement* is ideally suited for fixing and anchoring construction elements (e.g. hinges, shelf holders, rawl plugs, railings) and for quickly making good holes and cracks in mineral surfaces, e.g. lime, cement and gypsum plaster, concrete, air-entrained concrete, clay tiles, etc. *decotric fast setting Cement* cannot be used on surfaces made from wood, metal and plastic and coats of emulsion paint.

Technical specifications:

Basic raw materials:	Special cement mixture, fillers, additives
Apparent weight:	approx. 1.35g/cm ³
pH-value:	12–13
Mix ratio:	100 g powder in 25 ml water
Working time:	3-5 minutes at 20° Celsius
Bending tensile strength:	approx. 4.9 N/mm ²
Compressive strength:	approx. 17 N/mm ²

Preparation of surface: The surface must be firm and free of release agents (dust, formwork oil, etc.). Pre-treat highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free* or *LH Universal*.

Instructions for use: Pour clean, cold water into a clean container and sprinkle in *decotric fast setting Cement*. Immediately mix vigorously, until a smooth, lump-free mortar results. Immediately apply the mixed compound to the area to be repaired using a stopping knife and smooth the surface. Fixed construction elements can be loaded after 24 hours.

Clean tools in water immediately after use.

Important information: Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage: Store in a dry place! Keep the containers tightly sealed!

Available sizes:

1 kg collapsible box	003801001
5 kg paper bag	003802001