

## decofill Façade Filler

### decofill Fassade und Feuchtraum

Ready-to-use, weather-resistant synthetic resin filling compound for the wet room and outdoor area.

**Instructions for use:**

*decofill Façade Filler* is perfectly suitable for repairing, smoothing and coating uneven, rough ceilings, walls and façades as well as for secure filling of lime, cement and gypsum plaster. It can also be applied on all mineral surfaces (concrete, porous concrete, bricks, etc.) as well as on dispersion paints and gypsum plasterboards.

Not suitable for filling work on wood, metal, glass and plastic.

**Technical data:**

Components:	Synthetic resin dispersion, filling material and additives
Density:	1.78 g/cm <sup>3</sup>
pH value:	8
Consumption:	approx. 1.7 kg/m <sup>2</sup> at 1 mm strength of coating
GISBAU product code:	M - DF02

**Surface preparation:**

The surface must be dry, stable and free from parting compounds (dust, formwork release oil, etc.). Remove poorly adhering paints and loose plaster. Pre-fill deep holes in outdoor areas using *decofill Exterior* or *decomur Exterior Façade Filler*.

Strongly absorbent, sanding and chalking surfaces should be primed with *decotric Deeply Penetrating Primer – Solvent Free*.

**Application:**

Apply *decofill Façade Filler* up to a coating thickness of max. 5 mm using a smoothing spatula. Irregularities in thickness can be smoothed wet or felted down. Carry out subsequent paintwork and bonding only after the filled surface is completely dry.

Do not process below +5° Celsius sub-floor and room temperature!  
Clean tools with water immediately after use.

**Storage:**

Store in a cool, but frost-free place. Keep the containers tightly sealed!

**Available sizes:**

400 g                      034301001