

# decofill Elasto Elastic Filler

## decofill elasto - Riss- und Fugendicht

Permanently elastic, white sealing compound for filling cracks and joints in indoor and outdoor areas

**Instructions for use:** *decofill Elasto elastic filler* is perfectly suitable for filling joint gaps and cracks up to 5 mm in width between all mineral surfaces (such as concrete, plaster and masonry) as well as plasterboard panels, ceramic tiles, wood, polystyrene, lacquered surfaces, wallpapers, dispersion paints and synthetic resin plasters.

The material is weather-resistant after curing.

**Technical data:**

Components:	Acrylate emulsion
Density:	1.68 g/cm <sup>3</sup>
pH value:	approx. 8
GISBAU product code:	M – DF01

**Surface preparation:** The surface must be dry, stable and free from parting compounds (dust, formwork release oil, etc.). Remove old wallpapers, poorly adhering paints and loose plaster. Strongly absorbent, sanding and chalking surfaces should be primed using *decotric Deeply Penetrating Primer – Solvent Free*.

**Application:** *decofill Elasto Elastic Filler* in desired coating thickness and smoothen. Subsequent paintwork does not need any priming beforehand.

*decofill Elasto Elastic Filler* can be painted over with all commercially available acrylic, aromatic-free alkyd resin and dispersion paints.

Do not process below +5° Celsius sub-floor and room temperature!  
Clean tools with water immediately after use.

**Storage:** Keep cool but protected from frost! Keep container well closed!

**Available size:** PE tube of 330 g each      034501001