

## decotric Wood and MDF Filler decotric Holz- und MDF-Spachtel

Ready-to-use, solvent-free synthetic resin filling compound for smoothing and mending all wood and MDF surfaces in indoor areas.

Instructions for use: decotric Wood and MDF Filler is perfectly suitable for surface preparation on

wood and MDF surfaces for subsequent lacquering with acrylic and alkyd resin lacquers. *decotric Wood and MDF Filler* is easy to process, very easy to sand

and produces a stable surface for subsequent coatings.

Not suitable for filling work on metals, glass and plastic materials.

**Technical specification:** Components: Pure acrylate dispersion, filling material

Colours: MDF-brown
Density: approx. 1.8 g/cm³

pH value: 7.5-8.5

Consumption: approx. 1.8 kg/m² at 1 mm strength of coating

GISBAU product code: M-DF01

Surface preparation: The surface must be dry, stable and free from parting compounds (grease, dust,

etc.).

Prime raw and strongly absorbent wood using base coat for wood.

Application: Knead tube well before each use. Spread decotric Wood and MDF Filler using a

spatula (e.g. Japan Spreader) up to 3 mm coating thickness. In the case of deeper holes, a further coat application can be made after the first coat has dried through. The dried plaster layer is easy to sand and can be painted over

with all commercially available acrylic and alkyd resin lacquers.

Do not process below +5° Celsius sub-floor and room temperature!

Clean tools with water immediately after use.

Storage: Store in a cool, but frost-free place. Keep the containers tightly sealed!

Available size: PE tube of 400 g each 034401001