

## decofill Façade Structured Acrylic decofill Fassaden Strukturacryl

Single-component, white sealant with plaster-like structure of acrylic based material for filling cracks and joints in indoor and outdoor areas. Permanently elastic, can be painted over and is weather-resisting.

**Instructions for use:**

*decofill Façade Structured Acrylic* is perfectly suitable for filling connecting joints and cracks between all mineral surfaces (such as concrete, plaster and masonry) as well as dispersion and façade paints, synthetic mineral resin plasters and for structured connecting joints on windows, doors and the like. Thanks to its granular structure, the sealant adapts itself perfectly to the plaster look. The material is weather-resistant after curing. Not suitable for permanently moving joints.

**Technical data:**

Components:	Acrylate emulsion, mineral filling material
Density:	1.8 g/cm <sup>3</sup>
pH value:	approx. 8
Frost resistant at transport:	-15 °C
Temperature resistance after curing:	-20 °C – +75 °C
Breaking elongation:	50 % to DIN 53504
GISBAU product code:	M – DF01

**Surface preparation:**

Widen out existing cracks in a wedge-shaped manner. The surface must be dry, stable and free from parting compounds (dust, formwork release oil, etc.). Remove loose plaster components. Strongly absorbent, sanding and chalking surfaces should be primed using *decotric Deeply Penetrating Primer - solvent free*.

**Application:**

Work *decofill Façade Structured Acrylic* strongly into the crack and smoothen. Adapt the structure using a wet brush if necessary. Protect from rain and wetness until skin has formed. Subsequent paintwork does not need any priming beforehand.

*decofill Façade Structured Acrylic* can be painted over with all commercially available acrylic, aromatic-free alkyd resin and dispersion paints.

Clean tools with water after use. Do not process below +5 °C sub-floor and room temperature.

**Storage:**

Keep container well closed and cool but frost-protected. Temperature resistance during transport up to max. -15 °C.

**Available size:**

Cartridge of 310 ml	034901001
---------------------	-----------