

decotric Wallpaper Primer

Use:

Stabilizes friable, chalking and porous substrates and regulates suction. Facilitates adjustment of wallpaper strips and promotes uniform drying of wallpaper adhesive. High penetration depth. Siloxane-modified for optimum preservation of breathability. Suitable for all dry, mineral substrates (e.g. plaster, render and concrete) as well as gypsum plasterboard and other drylining board.

Properties:

- special primer for best wallpapering results
- stabilizes substrate
- regulates suction
- colourless

Technical data:

Raw material base: Hydrosol acrylate dispersion, water, siloxane, additives
 Density: Approx. 1 g/cm³
 pH value: 8 - 9

Substrate preparation:

Remove existing wallpaper, badly adhering coatings and loose plaster/render. Prior to priming, mask areas not to be treated as dried splashes are subsequently difficult to remove.

Application:

decotric Wallpaper Primer is supplied ready-for-use and can be applied by brush or suitable spray equipment. Only perform any necessary filling works after priming. To achieve uniformly absorbent substrates after patching, (re)treatment of patched surfaces with decotric Wallpaper Primer is recommended after full drying.

Consumption:

1 ltr suffices for approx. 10 m² for single coat, depending on substrate.

Note:

Do not use at building fabric and room temperatures below +5 °C. Wash tools with water immediately after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.decotric.de or from sds@decotric.de.

Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

Disposal:

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of liquid waste under EWC waste code: 08 01 12.

Item No.	EAN	Container size
037501001	4007955075028	2.5 ltr



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.