

decotric Alkaline Paint Stripper Powder decotric Strip Abbeizpulver

Alkali paint stripper for oil-based paints and synthetic resin-based paints. Effortlessly removes several layers of paint in one operation. Solvent free.

Instructions for use:

decotric Alkaline Paint Stripper Powder is ideally suited for removing paints made on a natural binder basis (e.g. oil-based paints, shellac) and synthetic resin-based paints. Ideal for restoring old pieces of furniture and for renovating painted or varnished wooden building elements such as door frames, etc.

Technical specifications:

Components:	Chalk, soda, wood fibres
Density:	approx. 0,40 g/cm ³
pH-value:	approx. 13
Mixing ratio:	1 kg powder to 2 l water
Usage:	approx. 500 g/m ² (depending on the thickness applied)

Application:

Stirring vigorously, sprinkle *decotric Alkaline Paint Stripper Powder* into cold water and continue stirring for a short time. Vigorously stir again after approx. 30 minutes' swelling time.

Apply *decotric Alkaline Paint Stripper Powder* to the area to be stripped of paint using a stopping knife or a brush. Remove any metal parts beforehand as they can be corroded by the paint stripping paste.

Leave the paint stripping paste to act for several hours, if the paint coats are very thick then leave overnight. To prevent the surface from drying out during the exposure time, we recommend covering the area being treated with foil or rewet it with water.

After an adequate exposure time the old coats of paint are pushed off using a stopping knife. The used paint stripping paste can be used again. Thoroughly clean the stripped areas with water. During the last rinse add vinegar to the water (0.1 l vinegar to 2.5 l water) to neutralise the paste. Only use stainless steel or plastic tools when using *decotric Alkaline Paint Stripper Powder*.

If used on veneered wood the veneer can come off. Dark discolorations can result if used on oak and other timbers with high tannic acid contents; however, these can be re-lightened using timber bleaching agents.

Do not use if the surface and/or room temperature is below + 10° Celsius. Lower temperatures reduce the stripping effect.

Clean tools thoroughly with water immediately after use.

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Store in a cool and dry place. Ensure opened containers are properly closed.

Available size:

1 kg collapsible box 006601000