

decotric Effect Glazes

decotric Effektlasuren

Glaze for a modern interior design

Instructions for use: A glaze on acrylate basis with a modern brighter effect that change depending

on the light. Suitable for ceilings and wall coatings on wallpapers, colours, brick, masonry, finery, Styrofoam and similar interior surfaces. The acrylic gets trans-

parent after drying and only the glitter remains visible.

Technical specifications: Components: Styrol-Acrylic- Dispersion, effect pigments, additive

Density: approx. 1.05 g/ml

pH-value 7-8

Usage: 80-120 ml/m² per coat

Surface preparation: The surface must be dry, firm and free of release agents (dust, formwork re-

lease oil, etc.). Do not apply decotric Effect Glaze until the wallpaper has com-

pletely dried.

Application: Shake well before use!

decotric Effect Glaze is ready to use and can be applied using a paint roller,

brush or spreader.

Do not use if the surface and/or room temperature are below + 5° C.

Clean tools in water immediately after use.

Storage: Store in a cool, but frost-free place. Keep the containers tightly sealed.

Article No.: 791 Pearl Effect 017003001

 792 Brilliant Effect
 017103001

 793 Diamont Effect
 017303001

 794 Rubin Effect
 017203001

 795 Smaragd Effect
 017503001

 796 Saphir Effect
 017403001

Available size: 1.5 I PP tin