

## decolor Tinting Paints

Synthetic resin emulsion paints in 25 colours and shades for indoor and outdoor use

**Instructions for use:**

*decolor Tinting Paints* are suitable for modern paint designs for façades and living space as well as for shading standard commercial, water-based emulsion, dispersion, latex, wall and ceiling paints and also for synthetic resin plasters and plastic.

The colours 901, 902, 903, 904, 905, 906 and 937 are also suitable for tinting silicate paints, whereby the amount added should not exceed 10 %. Observe the EN standard.

**Technical specifications:**

Components:	Synthetic resin emulsion, coloured pigments
Density:	approx. 1.40 g/cm <sup>3</sup>
pH-value:	approx. 8.5
Gloss unit:	Satin finish to DIN 53778
Scrubbing cycles:	> 5.000 DH, scrub resistant to EN 13300
Usage:	150 - 200 ml/m <sup>2</sup> per coat
GISBAU product code:	M-DF01

**Surface preparation:**

The surface must be dry, firm, dust and grease free. Remove old, peeling wall-papers and flaking coats of paint using *decotric Wallpaper Remover*. Make good cracks and holes using *decomur Interior Super Bonding Filler* or *decomur Exterior Filler*. Prime highly sanding, absorbent and chalking surfaces with *decotric penetrating primer - solvent free* or *decotric penetrating primer LH*.

**Preparation:**

*decolor Tinting Paints* can be applied with a brush, paint roller or a suitable spray gun. For undercoats the paints can be thinned with max. 10 % water. Apply the topcoat unthinned or with max. 5 % water added.

To tint white emulsion paints, stir in *decolor Tinting Paints* until the mix is homogeneous and use according to the instructions. Adding large quantities of *decolor Tinting Paints* to white, glossy emulsion paints can cause a reduction in the gloss. It is necessary to use the same white basic paint to achieve the same shade when remixing paint.

Due to their high organic pigment content, full colour paints in the colours sun yellow, orange, bright red and mint have a low hiding power. Adding 5-10 % white emulsion paint increases the hiding power. Only use the colours marked in the colour cards with an asterisk (\*) in full colour for outdoors.

Do not use if the surface and/or room temperature are less than + 5° Celsius!  
Clean tools in water immediately after use.

**Important information:**

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

**Storage:**

Store in a cool but frost-free place! Keep the containers tightly sealed!

**Shelf life**

2 years as of production date

**Available sizes:**

250 ml PE bottle	09XX01001
750 ml PE bottle	09XX02001