

pronatur Lehmfarbe is a natural white wall paint, which is ideal for spreading clay plasters.

- ▲ natural white, for interior, matt, high breathable
- ▲ free of solvents and plasticizers, without preservatives



Classification according to DIN EN 13 300:

Wet scrub resistance: class 4
contrast ratio: class 3 with a range of 7 m²/l
Degree of gloss: matt
Maximum grain size: fine

Instruction for use:

White, matt silicate wall and ceiling paint for indoor use. For mineral substrates (such as gypsum, lime- and cement plaster, masonry and concrete) as well as gypsum plasterboard and gypsum fiber boards and similar subsoils. Due to its microcrystalline structure, the coating has a high water vapour diffusion capacity and thus supports a pleasant room climate.

Components:

Water, Clay, marble powder, kaolin, mineral white pigment, modified vegetable oil, methylcellulose.

Surface preparation:

All surfaces have to be clean and load bearing. Do not remove stuck old paints, glue paints and loose cleanings. Prime strongly absorbing, sanding and chalking surfaces with pronatur primer.

Application:

pronatur Lehmfarbe can be diluted up to 10% with water as a pre-coat. Use as a final coat undiluted. If needed (for example on very dark, unequal or very absorbent surfaces) apply two coatings. Tintable up to max. 4% with universal tinting concentrates.

1. Stir well before use.
2. The application can be carried out with roller, brush, surface brush or spraying device. When spraying in the airless process, please use a sieve bag.
3. Clean the tools immediately after use with clear water, adding soap or detergent.

Consumption:

Depending on the surface and for one application ➤ approx. 1 l/ 6-8 m²

Important advices:

The drying time depends on the processing temperature. Relative humidity above 90%, especially in conjunction with low temperatures, can have a significant effect on the drying time and quality characteristics.



Important advices:

The usual safety precautions must also be observed when using low-pollutant products. Keep out of the reach of children. In the case of skin or eye contact, immediately rinse thoroughly with water. Wear protective clothing. Do not empty into drains. Free of fogging-active substances.

Contains preservatives: Methylisothiazolinones/Benzisothiazolinones. Can cause allergic reactions.

GISCODE: BSW20//M-DF01

CE VOC limit value for this product:
(cat. A/c, Wb) = 30 g/l (2010)
This product contains max 0,5 g/l VOC

Can be recoated after 6 to 12 hours.

Do not apply below +5° Celsius subfloor and room temperature.

Storage:

Keep cool but protect from frost! Keep bucket well closed. Best before: 3 years from date of manufacture (in an unopened condition and when properly stored).

Disposal:

Only empty buckets for recycling. Dried material residues can be disposed as construction and demolition waste or as household waste.

Order number:

107126	64	x	5,0 l	PE-bucket
107133	40	x	10,0 l	PE-bucket