

**pronatur Grundierung is a water-thinnable universal ground for pronatur clay color, pronatur inside white, pronatur vital white and pronatur clay-plaster.**

- ▲ **Based on sunflower oil, for inside, ready for use**
- ▲ **Free of solvents and plasticizers, low-emissions**
- ▲ **Solidifying, regulates absorbency, transparent drying**

#### Instruction for use:

Primer based on vegetable binders without synthetic resin additive. The pronatur primer creates a load-bearing and uniformly absorbent substrate, which is ideal for subsequent paints with pronatur clay color, pronatur Inside white, pronatur Vital White or pronatur clay plaster. Applicable to mineral substrates (such as gypsum, lime and cement plaster, masonry and concrete) as well as gypsum plasterboard and gypsum fiber boards and similar subfloors in the interior.

#### Binder:

Water, binder based on sunflower oil

#### Surface preparation:

All surfaces have to be clean, dry, sustainable and absorbent as well as release agent free. Non-solidifying or insufficiently adherent substrates must be completely removed. In case of doubt please do a test coating.

#### Application:

The pronatur primer is ready for use and is applied to the substrate undiluted with a brush or a paintbrush. Clean tools immediately after use with water. Remove accidental splashes immediately with water. Carry out the following work only after the primer has dried completely.

#### Consumption:

Depending on the surface and for one application ➤ approx. 1 l/7 m<sup>2</sup>

#### Important advices:

The drying time depends on the processing temperature. Relative humidity above 90%, especially in conjunction with low temperatures, can have a significant effect on the drying time and quality characteristics.

Do not apply below +5° Celsius subfloor and room temperature.

GISCODE: BSW20 // M-GF01



#### Important advices:

The usual safety precautions must also be observed when using low-pollutant products. Keep out of the reach of children. In case of skin or eye contact, immediately rinse thoroughly with water. Wear protective clothing. Do not empty into drains.

Contains preservatives: Methylisothiazolinones/Benzisothiazolinones. Can cause allergic reactions.

CE VOC limit value for this product:  
(cat. A/c, Wb) = 30 g/l (2010)  
This product contains max 1 g/l VOC

#### Storage:

Keep cool but protect from frost! Keep bucket well closed. Best before: 3 years from date of manufacture (in an unopened condition and when properly stored).

#### Disposal:

Only empty buckets for recycling. Dried material residues can be disposed as construction and demolition waste or as household waste.

#### Order number:

107225                      64    x    5,0 l                      PE-bucket