

## decomur Filler MT 75

Synthetic resin modified, gypsum-based joint filler for indoor use.

<b>Instructions for use</b>	<p><i>decomur Filler MT 75</i> is ideally suited for filling cracks and holes, for all-over smoothing and for gluing, jointing gypsum board, gypsum fiber boards and cement fiber boards, for concrete ceilings and for forming and modeling purposes. Gypsum board panels should be mounted stress free and we advise to use reinforcing strips (gauze). Always observe the gypsum board manufacturer's instructions for use. <i>decomur Filler MT 75</i> can be used on all mineral surfaces such as plaster, stone, concrete, air-entrained concrete, masonry, etc.</p> <p>Not suitable for filling glass, plastic, wood, metal and emulsion paint surfaces.</p>	
<b>Technical specifications:</b>	Basic raw materials:	Natural gypsum, methyl cellulose, synthetic resin
	Bulk density:	ca. 0,75 g/cm <sup>3</sup>
	pH-value:	7-8
	Mix ratio:	25 kg MT75 to 17.5 l water
	Consumption:	1 kg powder per 1 m <sup>2</sup> with thickness of 1 mm
	Working time:	approx. 75 min. at +20 °C
<b>CE-corresponding:</b>	Tensile bending strength	203 N according to EN 13963-3B
	CE-conform according to	EN 13963 – 3B
	CE-conform according to	EN 13279-1 – C7/20/2
<b>Preparation of surface:</b>	<p>The surface must be dry, firm and free of release agents (dust, formwork oil, etc.). Remove old wallpapers and falking coats of paint with <i>decotric Wallpaper Remover</i>. Remove loose plaster. Prime highly absorbent, sanding and chalking surfaces with <i>decotric Deeply Penetrating Primer – Solvent Free</i>.</p>	
<b>Instructions for use:</b>	<p>Pour clean, cold water into a container and sprinkle in <i>decomur Filler MT 75</i>. Stir vigorously until a smooth, lump-free mortar results. Use a firmer consistency to fill cracks and holes than for widespread filling. The filling compound can be applied with a filling knife or trowel after 2-3 minutes maturing time.</p> <p>Minor unevenness can be removed using a wet sponge board before the filler has completely hardened. After the filler has completely dried out the surface can be reground. It may be necessary to prime the improved areas or the whole surface using <i>decotric Deeply Penetrating Primer – Solvent Free</i> to avoid uneven drying of subsequent coats of paint of improving works.</p> <p>Do not use if the surface and/or room temperature is less than +5° Celsius. Clean tools in water immediately after use.</p>	
<b>Storage:</b>	Store in a dry place! Keep the containers tightly sealed.	
<b>Available size:</b>	25 kg paper bag - 003406073	