

decomur Fill+ Finish Filler ready

Area of application:

Ready-to-use, white all-round lightweight filler for interior surfaces. For smoothing plaster, concrete, aerated concrete and masonry as well as for full-surface levelling of plasterboard in surface qualities Q3-Q4. Also ideal for finish filling of pre-filled gypsum board joints in surface quality Q2 and for joint filling after Q1 of gypsum boards with the edge forms HRAK (Vario) and AK using joint cover strips. Can be used on all mineral substrates (e.g. concrete, gypsum, lime and cement plaster, brick, etc.), emulsion paints, synthetic resin plasters as well as on gypsum, gypsum fibreboard, cement fibreboard and similar dry construction boards.

Properties:

- for surface finishes Q1-Q4 in drywall construction
- fine, white and smooth
- Easy processing
- Very good sanding properties

Technical data:

Raw material base: Plastic dispersion, mineral Proportions, water and additives
 Density: approx. 1.25 - 1.35 g/cm³
 pH value: approx. 8

Substrate pre-treatment:

The substrate must be dry, stable and free of separating agents (dust, grease, formwork oil, etc.). Very smooth concrete, highly absorbent, sanding and chalking substrates and sanded surfaces with decotric Deep Primer LF. The cut edges of plasterboard should also be primed. Repair deep holes and break-outs with decomur gypsum levelling compounds.

Processing:

Stir before use and apply with a smoothing trowel or a suitable airless spraying device. When spraying, the application consistency can be adjusted by adding max. 1 litre of water per 20 kg container of filler. Application thickness max. 3 mm for surface qualities Q3-Q4 and for full-surface application.

Grinding recommendation:

After drying, the levelled surfaces can be sanded very easily. For optimum sanding results on large surfaces, we recommend using a disc sander (abrasive grit 150 or finer) at slow to medium speeds and low pressure.

Notes:

Do not process below +5 °C object and room temperature. Clean tools with water after use. Not suitable for levelling work on wood, glass, plastic and metal. Not suitable for levelling work on floors.

For safety-relevant data, please refer to the safety data sheet. Current safety data sheets are available on our website www.decotric.de or at sds@decotric.de

Storage:

Store opened containers tightly closed in a cool, frost-free place. Keep out of the reach of children.

Disposal:

Only dispose of empty containers for recycling. Dry material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues according to EWC waste code no. 08 04 10.

Article no.	EAN	Container size
032204001	4007955322047	20 kg
032202001	4007955322030	6 kg



Remark:

All information and data in this information sheet are based on our practical experience and laboratory tests and reflect the current state of the art. However, it can only general information and does not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place beyond our control, no legal liability can be derived from the information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective object conditions.