decotric Power Glass

Use:
Adhesive for all heavy and overcoatable wallpapers, renovation and reinforcing non-wovens, glassfibre and non-woven wallpapers.

Properties:
- with PVA polymer for high moisture resistance
- also ideal for damp spaces
- dries to transparent finish
- for brush application and wall-pasting with roller and spray

Technical data:

Raw material base:	Methyl cellulose, starch ether, plastic powder and additives
Bulk density:	Approx. 500 kg/cm³
pH value:	9

Substrate preparation:
Substrate shall be dry, solid, strong, level, uniformly absorbent and free from adhesion-impairing substances (e.g. dust, grease, mould oil). Remove existing wallpaper. Repair cracks, holes and irregularities with decotric fillers. Pretreat highly absorbent, friable and chalking substrates with decotric Primer – solvent-free.

Mixing ratio:
Stirring vigorously, briskly sprinkle pack contents into 7.5 ltr cold clean water and briefly continue to stir. After 20 minutes, thoroughly beat mix.

Application:
Application to wall covering: Apply adhesive in required thickness to rear face with pasting machine or brush. After prescribed soaking time, hang wallpaper strips with butted seams, pressing down evenly to remove entrapped air.

Application to substrate: Dimensionally stable wall coverings that require no softening time can also be applied by wall-pasting method. To do this, apply adhesive generously and uniformly to substrate over strip width with short-pile lambskin roller or suitable spray equipment. Place wall covering into adhesive bed and press down evenly to remove entrapped air.

Consumption:
500 g suffice for approx. 45 m².

Note:
Observance of wallpaper manufacturer's application guidelines is essential. Do not use at building fabric and room temperatures below +5 °C. Wash off adhesive residue with fresh water and rub down with dry cloth. Wash tools with water after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.decotric.de or from sds@decotric.de.

Storage:
Store in cool, though frost-free environment in properly sealed containers, out of reach of children.

Disposal:
Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 04 14.

Item No.	EAN	Container size
000904026	4007955767015	500 g

decotric GmbH, Im Schedetal 1, 34346 Hann. Münden
Tel. 05541 / 7003 -02, www.decotric.de

Status: 14.03.2023

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art.
They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.