

# Acrylic Joint Sealant

## Use:

For up to 30 mm wide joints and cracks. Ideal for sealing perimeter joints around windows, doors etc. For application to plaster, render, concrete, masonry, ceramic tiles, metal, wood, polystyrene, coated surfaces and emulsion paint coats.

## Properties:

- permanently elastic
- outstanding adhesion
- overcoatable
- for indoor and outdoor use
- white

## Technical data:

Raw material base: Polymer dispersion, inorganic fillers and additives  
Density: Approx. 1.7 g/cm<sup>3</sup>  
pH value: Approx. 7 – 9

## Substrate preparation:

Substrate shall be strong and free from dust and grease. Non-absorbent substrates shall be dry. Pre-wet absorbent substrates.

## Application:

Press Acrylic Joint Sealant into joint to be sealed and, if necessary, immediately smooth surface while moist. Immediately remove residue with damp cloth. Wash tools immediately with water. 12.5 % expansibility, skinning after approx. 20 minutes. Overcoatable after approx. 24 hours. Curing at rate of 2 mm per day – then permanently elastic.

## Note:

Do not use at temperatures below +5 °C. Wash tools with water after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at [www.pufas.de/www.decotric.de](http://www.pufas.de/www.decotric.de) or from [sds@pufas.de/sds@decotric.de](mailto:sds@pufas.de/sds@decotric.de).

## Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

## Disposal:

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 04 10. Do not allow to enter drains, sewers, surface waters or ground.

Item No.	EAN	Container size
034701001	4007955347019	310 ml



## Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.