

decotric Power Wall-Primer

decotric Klebkraft – Verstärker

- concentrate
- MC-acryl technology
- thixotropic gel
- transparent
- ready in 3 minutes

Instructions for use:

Special wallpapering primer for high-quality preparation of the substrate. Binds dust regulates absorbency and improves the adhesion of wallpaper adhesive.

Technical specifications:

Components: Methyl cellulose, plastic powder, additives
Bulk density: approx. 0.47 g/m³

Surface Preparation:

The substrate must be dry, firm, stable, even, evenly absorbent and free of dust and grease. Remove old wallpaper and paint. Fill cracks, holes and unevenness with decotric levelling compounds. Stabilise sanding and chalking substrates with decotric primer solvent free.

Application:

Quickly pour decotric Power Wall-Primer into 5 litres of cold water while stirring vigorously and continue stirring for a short time. Stir again after three minutes.

Apply with a suitable brush and let it dry for approximately one hour. Afterwards, the wallpaper can be applied as usual.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not process below +5° Celsius sub-floor and room temperature!

Clean any working equipment with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep out of reach of children and store in a dry place.

Available sizes:

125 g 4007955106128 110602173 REG

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.